

BLOXWICH FABRIC
Haberdashery & Greeting Cards
3, SAMUEL STREET,
TEL. BLOXWICH



ANGEL TOPS

in

Peter Pan Darling 4 Ply

No. P.346
WORKED IN DARLING
Shade 800

Instructions given for 46 cm. (18 inch) Chest, larger sizes given in brackets.
Where only one figure is given this applies to all sizes.

MATERIALS AND MEASUREMENTS

To Fit Chest Sizes.	46 18	51 20	cm. ins.
Peter Pan Darling 4 Ply.	Design No. 1. (Knitted) Design No. 2. (Crochet)	4 4	5 5 Balls Balls
DESIGN NO. 1. 2-4½ mm. (No. 7) and 2-3¼ mm. (No. 10) Aero Knitting Needles—46 cm. 18 inch size. 2-5 mm. (No. 6) and 2-3¼ mm. (No. 9) Aero Knitting Needles—(51) cm. (20) inch size. 5 Buttons. 4mm. Aero Crochet Hook. Ribbon.			
DESIGN NO. 2. 4 mm. Aero Crochet Hook. 3 Buttons. Ribbon.			
BOTH DESIGNS Length from Back of Neck.	24 9½	26-5 10½	cm. ins.
Sleeve Seam.	10 4	12-5 5	cm. ins.

The quantities of yarn stated are based on average requirements and are therefore approximate.

ABBREVIATIONS

K.=Knit; P.=Purl; st(s). = stitch(es); g.st.=garter stitch;
tog.=together; alt.=alternate; t.b.l.=through back of
loop; sl.1=slip one; p.s.s.o.=pass slipped stitch over; y.r.n.
=yarn round needle; y.o.n.=yarn over needle; y.fwd.=yarn
forward; patt.=pattern; ch.=chain; tr.=treble; h.tr.=
half treble; sp.=space; gr.=group (1 tr. 1 ch.) 3 times, 1 tr.
all into same st.; 0=No sts. or rows to be worked in that
particular size; cm.=centimetres; ins.=inches.

Success will be assured if you . . .

Use ONLY the Wendy or Peter Pan yarn specified. (We
cannot accept responsibility for an imperfect garment if any
other brand is used.)

Follow our instructions exactly, make certain you have the
right tension. Measure (without stretching) to see you're
working the right number of stitches as stated. Too many?—
use larger needles. Too few?—use finer needles. Once the
tension is right, the size will be right.

NOTE: Both Designs Backs and Fronts are worked in one
piece.

DESIGN NO. 1 (Knitted)

TENSION

11 sts. and 20 rows to 5 cm. (2 ins.) over g.st. on 4½ mm. (No.
7) Needles.

10 sts. and 18 rows to 5 cm. (2 ins.) over g.st. on 5 mm. (No.
6) Needles.

LEFT BACK (Commence at centre back)

Using 4½ mm. No. 7 (5 mm. No. 6) Needles, cast on 38 sts.
1st Row—K.29, P.1, * y.o.n., K.1, P.1, rept. from * to end

Commence Patt.

2nd Row (Wrong side)—K.1, * P.2 tog., y.o.n., K.1, rept.
from * to last 29 sts., P.1, K. to end.

3rd Row—K.29, P.1, * y.o.n., K.2 tog., P.1, rept. from * to
end.

4th and 6th Rows—As 2nd Row.

5th and 7th Rows—As 3rd Row.

8th Row—As 2nd Row.

9th Row—K.29, P.1, * sl.1, K.1, p.s.s.o., y.r.n., P.1, rept. from * to end.

10th Row—K.1, * y.r.n., P.2 tog. t.b.l., K.1, rept. from * to last 29 sts., P.1, K. to end.

11th, 13th and 15th Rows—As 9th Row.

12th, 14th and 16th Rows—As 10th Row.

17th Row—K.29, P.1, * y.o.n., sl.1, K.1, p.s.s.o., P.1, rept. from * to end.

Rows 2 to 17 form the patt. Work 2 more complete patterns then rows 2 to 8 once.

Shape Left Armhole

Next Row—Cast off 5 sts., patt. to end.

Keeping patt. correct, work 5 rows.

Next Row—Cast on 5 sts., patt. to end.

FRONT

Next Row—As 16th Row.

Next Row—As 17th Row.

Work 7 patterns.

Next Row—As 2nd Row.

Shape Right Armhole

Next Row—Cast off 5 sts., patt. to end.

Keeping patt. correct, work 5 rows.

Next Row—Cast on 5 sts., patt. to end.

RIGHT BACK

Work rows 10 to 17, then 3 more complete patterns. Cast off.

SLEEVES (Both alike)

Commencing at underarm seam.

Using 4½ mm. No. 7 (5 mm. No. 6) Needles, cast on 30 sts.

1st Row—K.23, P.1, * y.o.n., K.1, P.1, rept. from * to end.

Commence Pattern

2nd Row (Wrong side)—K.1, * P.2 tog., y.o.n., K.1, rept. from * to last 23 sts., P.1, K. to end.

3rd Row—K.23, P.1, * y.o.n., K.2 tog., P.1, rept. from * to end.

4th and 6th Rows—As 2nd Row.

5th Row—As 3rd Row.

7th Row—K.23, P.1, * sl.1, K.1, p.s.s.o., y.r.n., P.1, rept. from * to end.

8th Row—K.1, * y.r.n., P.2 tog. t.b.l., K.1, rept. from * to last 23 sts., P.1, K. to end.

9th and 11th Rows—As 7th Row.

10th and 12th Rows—As 8th Row.

13th Row—K.23, P.1, * y.o.n., sl.1, K.1, p.s.s.o., P.1, rept. from * to end.

Rows 2 to 13 form the patt. Work 2 more patterns then rows 2 to 12 once. Cast off.

Join sleeve seams by top sewing leaving 2.5 cm. (1 inch) open at sleeve top.

Pin sleeves into position placing top of open seam to top of armhole and sleeve seam to centre of underarm. Sew in by top sewing.

Yoke

With right side of work facing commencing at left back, using 3¼ mm. No. 10 (3½ mm. No. 9) Needles, pick up and K.31 sts. across left back picking up approximately one st. for every 2 rows of g.st., 26 sts. across sleeve top, 60 sts. along front, 26 sts. across sleeve top and 31 sts. across right back. 174 sts.

K. 3 Rows.

Next Row (Make holes)—K.1, * y.fwd., K.2 tog., rept. from * to last st., K.1.

Next Row—Knit.

Next Row (Dec. Row)—K.6, * K.2 tog., K.6, rept. from * to end. 153 sts.

K. 5 Rows.

Next Row (Dec. Row)—K.3, * K.2 tog., K.3, rept. from * to end. 123 sts.

K. 5 Rows.

Next Row (Dec. Row)—K.1, * K.2 tog., K.2, rept. from * to last 2 sts., K.2 tog. 92 sts.

K. 5 Rows.

Next Row (Dec. Row)—K.1, * K.2 tog., K.1, rept. from * to last st., K.1. 62 sts.

K. 4 Rows. Cast off.

DESIGN NO. 2 (Crochet)

TENSION

9 h.tr.s. and 8 rows to 5 cm. (2 ins.) on 4 mm. Hook.

LEFT BACK (Commence at centre back)

Using 4.0 mm. hook, make 27 (31) ch.

Foundation Row (Right side)—1 h.tr. into 2nd ch. from hook, 1 h.tr. into each ch. to end, turn. 26 (30) sts.

Next Row—1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn.

The last row forms the patt. Work 16 (18) more rows.

Shape Left Armhole

****Next Row**—Sl.st. over 5(6) sts. and into next h.tr., work 1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn. Work 2 rows.

Next Row—1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., make 6 (7) ch., turn.

Next Row—1 h.tr. into 2nd ch. from hook, 1 h.tr. into next 4 (5) ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn. **

FRONT

Work 39 (41) Rows.

Shape Right Armhole

Work from ** to ** once.

RIGHT BACK

Work 18 (20) more rows in patt. Fasten off.

Inches
CM
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23

Border

With right side of work facing, commencing at lower edge right back, rejoin yarn. Work 85 (89) d.c. evenly along lower edge, turn.

Commence Patt.

1st Row—3 ch. (counts as first tr.), miss one d.c., * 1 gr. into next d.c., miss one d.c., 1 tr. into next d.c., miss one d.c., rept. from * to last 3 d.c., 1 gr. into next d.c., miss 1 d.c., 1 tr. into turning ch., turn.

2nd Row—3 ch., 1 gr. into centre ch. sp. of gr., * 1 tr. into tr., 1 gr. into centre ch. sp. of gr., rept. from * to last st., 1 tr. into top of 3 ch., turn.

Rept. the last row twice more. Fasten off.

SLEEVES (Both alike)

Commencing at underarm seam.

Using 4.0 mm. hook, make 15 (19) ch.

Foundation Row (Right side)—1 h.tr. into 2nd ch. from hook, 1 h.tr. into each ch. to end, turn. 14 (18) sts.

Next Row—1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn.

Rept. the last row 20 (24) times more.

Fasten off.

Sleeve Border

With right side of work facing, rejoin yarn at seam.

Using 4.0 mm. hook, work 21 (25) d.c. evenly on row ends along lower edge.

Work 4 rows in patt. as given for lower edge of Backs and Front. Fasten off.

Join sleeve seams by top sewing leaving 2.5 cm. (1 inch) open at sleeve top.

Pin sleeves into position placing top of open seam to top of armhole and sleeve seam to centre of underarm, sew in by top sewing.

Yoke

With right side of work facing commencing at centre back, using 4.0 mm. hook, rejoin yarn. Work 18 (19) d.c. evenly across left back, 22 (25) d.c. across sleeve top, 37 (39) d.c. along front, 22 (25) d.c. across sleeve top and 18 (19) d.c. across right back, turn. 117 (127) d.c.

Next Row (Make holes)—3 ch., miss 1 d.c., * 1 tr. 1 ch. into next d.c., miss 1 d.c., rept. from * to last st., 1 tr. into top of turning ch., turn.

Next Row (Dec. Row)—1 ch., * miss next ch. sp., 1 h.tr. into next tr., 1 h.tr. into next ch. sp., 1 h.tr. into next tr., 1 h.tr. into next ch. sp., miss 1 tr., 1 h.tr. into next ch. sp., 1 h.tr. into next tr., 1 h.tr. into next ch. sp., 1 h.tr. into next tr., rept. from * to last 6 sts. miss next ch. sp., 1 h.tr. into next tr., 1 h.tr. into next ch. sp., 1 h.tr. into next tr., miss next ch. sp., 1 h.tr. into turning ch., turn. 94 (102) sts.

Next Row (Dec. Row)—1 ch., 1 h.tr. into next h.tr., * 1 h.tr. into next h.tr., h.tr. 2 tog., 1 h.tr. into each of next 2 h.tr., rept. from * to last 2 (5) sts., 1 h.tr. into next h.tr., 1 h.tr. into turning ch., (1 h.tr. into next h.tr., h.tr. 2 tog., 1 h.tr. into next h.tr., 1 h.tr. into turning ch.), turn. 76 (82) sts.

Next Row—1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn.

Next Row (Dec. Row)—1 ch., 1 h.tr. into each of next 2 h.tr., * h.tr. 2 tog., 1 h.tr. into each of next 2 h.tr., rept. from * to last 1 (3) sts., 1 h.tr. into turning ch. (h.tr. 2 tog., 1 h.tr. into turning ch.), turn. 58 (62) sts.

Next Row—1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn.

Next Row (Dec. Row)—1 ch., 1 h.tr. into next h.tr., * h.tr. 2 tog., 1 h.tr. into next h.tr., rept. from * to last 2 (3) sts., 1 h.tr. into next h.tr., 1 h.tr. into turning ch. (h.tr. 2 tog., 1 h.tr. into turning ch.), turn. 40 (42) sts.

Next Row—1 ch., 1 h.tr. into each h.tr. to end, 1 h.tr. into turning ch., turn.

Next Row (Picot edging)—1 ch., 1 d.c. into next h.tr., * 3 ch., 1 d.c. into 3rd ch. from hook, 1 d.c. into each of next 2 h.tr., rept. from * to last 2 sts., 3 ch., 1 d.c. into 3rd ch. from hook, 1 d.c. into next h.tr., 1 d.c. into turning ch. Fasten off.

PRESSING

With wrong side facing, pin out all pieces to measurements given. Press as instructions.

MAKING UP

Both Designs

Using 4 mm. hook, work 1 row of d.c. evenly up left back, turn with 1 ch. work 1 more row of d.c. Fasten off.

Mark position for buttons on left back, the first one at commencement of yoke, the last one at neck and one more equally spaced between.

Using 4 mm. hook, work 2 rows of d.c. on right back, working buttonholes to correspond with positions marked for buttons on the 2nd row as follows:—

1 ch., miss 1 d.c. Fasten off.

Thread ribbon through holes round yoke.

Sew on buttons to correspond with buttonholes.

Design No. 1

Sew buttons on front of yoke as illustrated.

Press seams lightly.

WASHING AND PRESSING INSTRUCTIONS		
	WASHING	PRESSING
PETER PAN DARLING	 Warm water, hand or machine wash, short spin, do not wring, dry flat.	 Use a dry cloth and cool iron.



Our Knitting Bureau will gladly give you any assistance or advice on Wendy Designs if queries are accompanied by a Wendy or Peter Pan Ball Band and a stamped addressed envelope.

CARTER & PARKER LTD, GUISELEY, YORKS.

Prices apply only in Great Britain and Northern Ireland

Printed in England

© CARTER PARKER LIMITED