

3047

25 CENTS

SIRDAR Wonderland

9/12 Months for Boy or Girl

FOUR PLY



IMPORTANT. SIRDAR LIMITED CANNOT ACCEPT RESPONSIBILITY FOR THE FINISHED PRODUCT IF ANY YARN OTHER THAN SIRDAR IS USED. IT IS ESSENTIAL TO WORK TO THE STATED TENSION.

Blue V Neck and Pink Round Neck

To Fit	21	ins
Actual size	22	ins
Full length	12	10½ ins
Sleeve length (adjustable)	8½	7 ins

Blue V Neck

WONDERLAND Nylon 4 ply	4	20gm balls
1 Pair No. 9 and No. 11 Knitting Needles.		
WONDERLAND Courtelle 4 ply	4	20gm balls
1 Pair No. 10 and No. 12 Knitting Needles.		
4 Buttons.		

Pink Round Neck

WONDERLAND Nylon 4 ply	5	20gm balls
1 Pair No. 9 and No. 11 Knitting Needles.		
WONDERLAND Courtelle 4 ply	5	20gm balls
1 Pair No. 10 and No. 12 Knitting Needles.		
1 Spare Needle with points at each end. 5 Buttons.		

The quantities of yarn stated are based on average requirements and are therefore approximate.

ABBREVIATIONS

K knit, p purl, sts stitches, tog together, s1 slip one stitch knitways, st-st stocking stitch (1 row knit, 1 row purl), reversed st-st reversed stocking stitch (1 row purl, 1 row knit), cont continue, beg beginning, alt alternate, foll following, rep repeat, patt pattern, psso pass slipped stitch over, yfwd yarn forward, inc increasing, dec decreasing.

After casting off stitches for shaping, one stitch will remain on the right hand needle which is not included in the instructions that follow.

ALTERNATIVE NEEDLES RECOMMENDED. SELECT YOUR NEEDLE SIZE ACCORDING TO YARN CHOSEN—SEE MATERIALS.

BLUE V NECK TENSION

The tension for this design is 7½ stitches to one inch measured over st-st.

Check your tension — if less stitches use a finer needle, if more use a coarser needle.

THE BACK

Using No. 11 or 12 needles cast on 73 sts and work 12 rows in k1, p1 rib.

Change to No. 9 or 10 needles.

**

1st Row. S1, k1, * yfwd, s1, k1, psso, k5, k2tog, yfwd, k1, rep from * to last st, k1.

2nd and Every Alt Row. S1, purl to last st, k1.

3rd Row. S1, k2, * yfwd, s1, k1, psso, k3, k2tog, yfwd, k3, rep from * to end of row.

5th Row. S1, k3, * yfwd, s1, k1, psso, k1, k2tog, yfwd, k5, rep from * to last 9 sts, yfwd, s1, k1, psso, k1, k2tog, yfwd, k4.

7th Row. S1, k4, * yfwd, s1, k2tog, psso, yfwd, k7, rep from * to last 8 sts, yfwd, s1, k2tog, psso, yfwd, k5.

9th Row. S1, k1, * yfwd, s1, k1, psso, k2tog, yfwd, k1, rep from * to last st, k1.

10th Row. S1, purl to last st, k1.

Rep 9th and 10th rows 4 times, then from 3rd to 7th row (inclusive) once.**

24th Row. S1, p3, (inc once in next st purlways, p6) 9 times, inc once in next st purlways, p4, k1. (83 sts). Work in st-st until work measures 5¾ inches from commencement, ending on wrong side. 7½"

Shape for the Armholes

Cast off 4 sts at beg of next 2 rows. Work 26 rows dec once at each end of next and every alt row. (49 sts). Work 16 rows dec once at each end of every row. (17 sts). Cast off.

THE LEFT FRONT

Using No. 11 or 12 needles cast on 33 sts and work 12 rows in k1, p1 rib.

Change to No. 9 or 10 needles and rep from ** to ** as given for The Back once.

24th Row. S1, p3, (inc once in next st purlways, p3) 7 times, k1. (40 sts).

Work in st-st until work measures same as The Back to armhole, ending on wrong side.

SIRDAR

Shape for the Armhole

Cast off 4 sts at beg of next row. Work 1 row. Work 6 rows dec once at armhole edge in next and every alt row. Work 20 rows dec once at armhole edge in next and every alt row and front edge in next and every foll 6th row. (19 sts).

Work 14 rows dec once at armhole edge in every row and front edge in 5th and foll 6th row. (3 sts).

Next Row. K2tog, k1.

Next Row. K2tog. Fasten off.

THE RIGHT FRONT

Work exactly as given for The Left Front reversing patt and all shapings.

THE SLEEVES (Both alike)

Using No. 11 or 12 needles cast on 41 sts and work 14 rows in k1, p1 rib inc once at each end of last row. (43 sts). Change to No. 9 or 10 needles and rep from ** to ** as given for The Back once.

24th Row. S1, p4, (inc once in next st purlways, p7) 4 times, inc once in next st purlways, p4, k1. (48 sts). Work in st-st inc once at each end of 5th and every foll 4th row to 60 sts.

Work straight until sleeve measures 7 inches, or length required, ending on wrong side.

Shape for the Top

Cast off 4 sts at beg of next 2 rows. Work 40 rows dec once at each end of next and every alt row. Work 2 rows dec once at each end of every row. (8 sts). Cast off.

TO MAKE UP

Read Pressing Instructions. Sew up side and sleeve seams. Sew in sleeves.

THE BUTTONHOLE BORDER

Using No. 11 or 12 needles cast on 7 sts.

1st Row. S1, (k1, p1) twice, k2.

2nd Row. S1, (p1, k1) 3 times.

Rep 1st and 2nd rows once.

5th Row. S1, k1, p1, cast off 1 st, k2.

6th Row. S1, p1, k1, cast on 1 st, k1, p1, k1.

Rep 1st and 2nd rows 9 times.*** Rep from *** to *** twice, 5th and 6th rows once, then 1st and 2nd rows until border is of sufficient length to go up front, across sleeve top and halfway across back of neck. Cast off.

THE BUTTON BORDER

Work exactly as given for The Buttonhole Border omitting Buttonholes.

TO COMPLETE

Sew ends of borders together, placing seam to centre back of neck, top buttonhole $\frac{1}{2}$ inch below first front dec, sew borders in position. Sew on buttons.

PINK ROUND NECK

TENSION

The tension for this design is

7½ stitches to one inch measured over reversed st-st.

Check your tension – if less stitches use a finer needle, if more use a coarser needle.

THE BACK

Using No. 11 or 12 needles cast on 99 sts and work 12 rows in k1, p1 rib.

Change to No. 9 or 10 needles.

1st Row. S1, p9, (k8, p4) twice, k8, p15, (k8, p4) twice, k8, p9, k1.

2nd Row. S1, k9, p8, (k4, p8) twice, k15, p8, (k4, p8) twice, k10.

3rd Row. S1, p9, * slip next 2 sts onto a spare needle and leave at back of work, k2, then k2 from spare needle (this will now be termed "cable back"), "cable back", p4, * rep from * to * once, ("cable back") twice, p15, rep from * to * twice, ("cable back") twice, p9, k1.

4th Row. S1, k9, p8, (k4, p8) twice, k15, p8, (k4, p8) twice, k10.

5th Row. S1, p9, * k2, slip next 2 sts onto a spare needle and leave at front of work, k2, then k2 from spare needle (this will now be termed "cable front"), k2, p4, * rep from * to * once, k2, "cable front", k2, p15, rep from * to * twice, k2, "cable front", k2, p9, k1.

6th Row. S1, k9, p8, (k4, p8) twice, k15, p8, (k4, p8) twice, k10.

From 3rd to 6th row (inclusive) forms reversed st-st and patt panels. Cont until work measures 5½ inches from commencement, ending with 6th row of patt.

Shape for the Armholes

Cast off 4 sts at beg of next 2 rows. Work 8 rows dec once at each end of next and every alternate row. (83 sts). Work 34 rows dec once at each end of every row. (15 sts). Cast off.

THE LEFT FRONT

Using No. 11 or 12 needles cast on 47 sts and work 12 rows in k1, p1 rib inc once at end of last row. (48 sts). Change to No. 9 or 10 needles.

1st Row. S1, p9, (k8, p4) twice, k8, p5, k1.

2nd Row. S1, k5, p8, (k4, p8) twice, k10.

3rd Row. S1, p9, * ("cable back") twice, p4, * rep from * to * once, ("cable back") twice, p5, k1.

4th Row. S1, k5, p8, (k4, p8) twice, k10.

5th Row. S1, p9, (k2, "cable front", k2, p4) twice, k2, "cable front", k2, p5, k1.

6th Row. S1, k5, p8, (k4, p8) twice, k10.

From 3rd to 6th row (inclusive) forms reversed st-st and patt panel. Cont until work measures same as The Back to armhole, ending with 6th row of patt.

Shape for the Armhole

Cast off 4 sts at beg of next row. Work 1 row straight. Work 8 rows dec once at armhole edge in next and every alt row. (40 sts). Work 16 rows dec once at armhole edge in every row. (24 sts).

Shape the Neck

Work 5 rows dec once at each end of every row. (14 sts). Work 11 rows dec once at armhole edge only in every row. (3 sts).

SIRDAR

*The price set out or referred to herein is a recommended price only and there is no obligation to comply with the recommendation.

Next Row. K2tog, k1.
Next Row. K2tog. Fasten off.

THE RIGHT FRONT

Work exactly as given for The Left Front reversing all shapings and working patt thus:

1st Row. S1, p5, k8, (p4, k8) twice, p9, k1.
2nd Row. S1, k9, (p8, k4) twice, p8, k6.
3rd Row. S1, p5, ("cable back") twice, * p4, ("cable back") twice, rep from * to * once, p9, k1.
4th Row. S1, k9, (p8, k4) twice, p8, k6.
5th Row. S1, p5, k2, "cable front", k2, (p4, k2, "cable front", k2) twice, p9, k1.
6th Row. S1, k9, (p8, k4) twice, p8, k6.
From 3rd to 6th row (inclusive) forms reversed st-st and patt panel. Cont in patt and complete as given for The Left Front.

THE SLEEVES (Both alike)

Using No. 11 or 12 needles cast on 41 sts and work 13 rows in k1, p1 rib.

Next Row. S1, (p1, k1, p1, inc once in next st) 9 times, (p1, k1) twice. (50 sts).

Change to No. 9 or 10 needles.

1st Row. S1, p8, (k8, p4) twice, k8, p8, k1.
2nd Row. S1, k8, p8, (k4, p8) twice, k9.
3rd Row. S1, p8, * ("cable back") twice, p4, * rep from * to * once, ("cable back") twice, p8, k1.
4th Row. S1, k8, p8, (k4, p8) twice, k9.
5th Row. S1, p8, (k2, "cable front", k2, p4) twice, k2, "cable front", k2, p8, k1.
6th Row. S1, k8, p8, (k4, p8) twice, k9.
From 3rd to 6th row (inclusive) forms reversed st-st and patt panel. Cont inc once at each end of next and every foll 4th row (working extra sts in reversed st-st) to 68 sts. Work straight until sleeve measures 7 inches, or length required, ending with 6th patt row.

Shape for the Top

Cast off 4 sts at beg of next 2 rows. Work 34 rows dec once at each end of next and every alt row. (26 sts).
Work 8 rows dec once at each end of every row. (10 sts). Cast off.

TO MAKE UP

Read Pressing Instructions. Sew up side and sleeve seams. Sew in sleeves.

THE BUTTONHOLE BORDER

Using No. 11 or 12 needles cast on 7 sts.

1st Row. S1, (k1, p1) twice, k2.

2nd Row. S1, (p1, k1) 3 times.
Rep 1st and 2nd rows once.

**

5th Row. S1, k1, p1, cast off 1 st, k2.

6th Row. S1, p1, k1, cast on 1 st, k1, p1, k1.
Rep 1st and 2nd rows 10 times.** Rep from ** to ** twice, 5th and 6th rows once then 1st and 2nd rows 9 times. Do not break off yarn for a Girl. Break off yarn for a Boy. Leave these sts on a thread.

THE BUTTON BORDER

Work exactly as given for The Buttonhole Border omitting Buttonholes. Do not break off yarn for a Boy. Break off yarn for a Girl. Leave these sts on a thread.

THE NECKBAND

With right side facing, using No. 11 or 12 needles, work across 7 sts left on a thread for The Buttonhole Border for a Girl and The Button Border for a Boy as follows: s1, (k1, p1) 3 times, pick up and knit 16 sts evenly along right side of neck, 10 sts across sleeve top, 15 sts from 15 cast off sts at back of neck, 10 sts across other sleeve top, 16 sts evenly along left side of neck and work across 7 sts left on a thread for The Button Border for a Girl and The Buttonhole Border for a Boy as follows: (p1, k1) 3 times, k1. (81 sts).

1st Row. S1, * p1, k1, rep from * to end of row.

For a Girl

2nd Row. S1, k1, p1, cast off 1 st, k1, * p1, k1, rep from * to last st, k1.

3rd Row. S1, * p1, k1, rep from * to last 3 sts, cast on 1 st, k1, p1, k1.

For a Boy

2nd Row. S1, k1, * p1, k1, rep from * to last 5 sts, p1, cast off 1 st, k2.

3rd Row. S1, p1, k1, cast on 1 st, k1, * p1, k1, rep from * to end of row.

For Boy or Girl

Work 2 rows k1, p1 rib. Cast off.

TO COMPLETE

Sew Front Borders in position. Sew on buttons.

GENERAL PRESSING INSTRUCTIONS

NYLON — under dry cloth — warm iron.

COURTELLE — under dry cloth — warm iron.

SIRDAR LIMITED

P.O. BOX No. 31 WAKEFIELD

SIRDAR WOOLS (PTY) LTD
P.O. BOX No. 49072 ROSETTENVILLE JOHANNESBURG

SIRDAR WOOLS (AUSTRALIA) PTY LTD
P.O. BOX No. 472 GOULBURN, N.S.W.