



Teddy



KNITTING

YARNS

DOUBLE
KNITTING

645



BABY'S PATTERNED, PLAIN AND LACY COATS

Note: figures in brackets refer to the larger sizes. Where only one set of figures is given this applies to all sizes.

MEASUREMENTS

To fit chest	35	40	46	cm
	14	16	18	inch
Length from back neck	24	25	25.5	cm
	9½	9¾	10	inch
Sleeve seam	11.5	11.5	12.5	cm
	4½	4½	5	inch

MATERIALS

YARN AMOUNTS—See back page

1 pair each size 3 and 3¾ mm (11 and 9) needles. Stitch holders. Cable needle for Patterned Coat. 4 buttons. Ribbon.

TENSION

Patterned Coat: 32 sts and 32 rows to 10 cm (4 inches) measured over pattern using size 3¾ mm (9) needles.

Plain and Lacy Coats: 24 sts and 32 rows to 10 cm (4 inches) measured over stocking stitch using size 3¾ mm (9) needles.

KNIT A TENSION SQUARE, IF TOO LARGE USE A FINER NEEDLE, IF TOO SMALL USE A THICKER NEEDLE.

ABBREVIATIONS

k=knit; p=purl; st(s)=stitch(es); patt=pattern; beg=beginning; dec=decrease; st st=stocking stitch; rep=repeat; T3F=slip next st onto cable needle and hold at front of work, p2 then k1 from cable needle; T3B=slip next 2 sts onto cable needle and hold at back of work k one st then p 2 sts from cable needle; 0=no stitches; sl 1=slip one stitch; rem=remaining; tog=together; yn fwd=yarn forward; g st=garter stitch (every row knit); C6B=slip next 3 sts onto cable needle and hold at back of work, k3 then k3 from cable needle.

PATTERNED COAT

BACK

With size 3¾ mm needles cast on 64 (76) (84) sts and commence patt.

1st row: p4 (4) (2) * k2 p4 rep

from * to last 0 (0) (4) sts k0 (0) (2) p0 (0) (2).

2nd row: k4 (4) (2) * p2 k4 rep from * to last 0 (0) (4) sts p0 (0) (2) k0 (0) (2).

3rd row: p2 (2) (0) * T3B T3F rep from * to last 2 (2) (0) sts p2 (2) (0).

4th row: k2 (2) (0) p1 * k4 p2 rep from * to last 7 (7) (5) sts k4 p1 k2 (2) (0).

5th row: p2 (2) (0) k1 * p4 k2 rep from * to last 7 (7) (5) sts p4 k1 p2 (2) (0).

6th row: as 4th row.

7th row: p2 (2) (0) * T3F T3B rep from * to last 2 (2) (0) sts p2 (2) (0).

8th row: as 2nd row.

These 8 rows form the patt.

Continue in patt (throughout) until back measures approximately 15 cm from beg ending with an 8th patt row.

Shape sleeves

NOTE: Cable method of casting on.

Take the needle with the sts on it in the left hand * insert the right hand needle between the first 2 sts on the left hand needle. Draw a loop through with right hand needle and place this loop on the left hand needle. Rep from * until the required number of sts are cast on.

Using cable method cast on 30 (30) (36) sts [94 (106) (120) sts].

Next row: work 1st row of patt.

Using cable method cast on 30 (30) (36) sts [124 (136) (156) sts].

Next row: work 2nd row of patt.

Continue without further shaping until back measures 24 (25) (25.5) cm from beg ending with a wrong side row.

Next row: cast off 48 (54) (64) sts patt 28 sts cast off rem 48 (54) (64) sts.

Leave rem 28 sts on a holder.

LEFT FRONT

With size 3¾ mm needles cast on 30 (36) (40) sts and commence patt.

1st row: p4 (4) (2) * k2 p4 rep from * to last 2 sts k2.

2nd row: sl 1 p1 * k4 p2 rep from * to last 4 (4) (2) sts k4 (4) (2).

3rd row: p2 (2) (0) * T3B T3F rep from * to last 4 sts T3B k1.

4th row: sl 1 k2 * p2 k4 rep from * to last 3 (3) (1) sts p1 k2 (2) (0).

5th row: p2 (2) (0) k1 * p4 k2 rep from * to last 3 sts p2 k1.

6th row: as 4th row.

7th row: p2 (2) (0) * T3F T3B rep from * to last 4 sts T3F k1.

8th row: as 2nd row.

These 8 rows form the patt.

Continue in patt (throughout) until front measures same as back to shape sleeve ending with an 8th patt row.

Shape sleeve

See NOTE on back of coat.

Using cable method cast on 30 (30) (36) sts [60 (66) (76) sts].

Next row: work 1st row of patt.

Next row: work 2nd row of patt.

Continue in patt until front measures 4 (4.5) (5) cm from cast on edge of sleeve ending with a right side row.

Shape neck

Next row: patt 5 sts slip these 5 sts to a safety pin, patt to end.

*** Work 7 rows dec one st at neck edge every row [48 (54) (64) sts].

Work without further shaping until front measures same as back ending with a wrong side row.

Cast off rem sts.

RIGHT FRONT

With size 3¾ mm needles cast on 30 (36) (40) sts and commence patt.

1st row: sl 1 k1 * p4 k2 rep from * to last 4 (4) (2) sts p4 (4) (2).

2nd row: k4 (4) (2) * p2 k4 rep from * to last 2 sts p1 k1.

3rd row: sl 1 T3F * T3B T3F rep from * to last 2 (2) (0) sts p2 (2) (0).

4th row: k2 (2) (0) p1 * k4 p2 rep from * to last 3 sts k3.

5th row: sl 1 p2 * k2 p4 rep from * to last 3 (3) (1) sts k1 p2 (2) (0).

6th row: as 4th row.

7th row: sl 1 T3B * T3F T3B rep from * to last 2 (2) (0) sts p2 (2) (0).

8th row: as 2nd row.

These 8 rows form the patt.

Continue in patt (throughout) until front measures same as back to shape sleeve ending with a 1st patt row.

Shape sleeve

See NOTE on back of coat.

Using cable method cast on 30 (30) (36) sts [60 (66) (76) sts].

Next row: work 2nd row of patt.

Continue in patt until front measures 4 (4·5) (5) cm from cast on edge of sleeve ending with a wrong side row.

Shape neck

Next row: patt 5 sts slip these 5 sts to a safety pin, patt to end.

Next row: patt to end.

Complete as given from *** on left front.

CABLE BORDER

(worked over 8 sts)

1st row: sl 1 k to end.

2nd row: sl 1 p to last st k1.

Rep last 2 rows once more.

5th row: sl 1 C6B k1.

6th row: as 2nd row.

These 6 rows form cable border patt.

SHOULDER INSERT

(make two)

With size 3 $\frac{3}{4}$ mm needles cast on 8 sts and work cable border patt until band is long enough to fit along cast off edge of sleeve from cuff to neck, ending with a wrong side row.

Break off yarn and leave these sts on a safety pin.

With right side of left and right fronts facing sew shoulder inserts (with cast on edge at cuff and sts left on safety pin at neck edge) to cast off edge of sleeve, beg at cuff and ending at neck edge.

With right side of back facing, sew cast off edges of sleeves to shoulder inserts, beg at cuff and ending at neck edge.

SLEEVE EDGING

(make two)

With size 3 $\frac{3}{4}$ mm needles cast on 8 sts and work cable border patt until band is long enough to fit along bottom edge of sleeve ending with a wrong side row.

Cast off and sew in place.

FRONT BORDERS

(make two)

With size 3 $\frac{3}{4}$ mm needles cast on 8 sts and work cable border patt

until band is long enough to reach up front to neck shaping ending with a wrong side row.

Leave these sts on a safety pin. Sew borders in position.

NECKBAND

With size 3 mm needles and right side of work facing k dec 3 sts evenly across right front border, k across 5 sts left on safety pin, pick up and k 10 sts up right front neck, k dec 3 sts evenly across right shoulder insert cable, k dec 5 sts evenly across back neck holder, k dec 3 sts evenly across left shoulder insert cable, pick up and k 10 sts down left front neck, k across 5 sts left on safety pin and k dec 3 sts evenly across left front border [73 sts].

Work 2 rows in g st. Cast off.

PLAIN COAT

BACK

With size 3 mm needles cast on 48 (54) (60) sts and work 2 rows in g st. Change to size 3 $\frac{3}{4}$ mm needles and continue in st st (throughout) until back measures 15 cm from beg ending with a wrong side row.

Shape sleeves

See NOTE on back of Patterned Coat.

Using cable method cast on 23 (23) (26) sts [71 (77) (86) sts].

Next row: knit.

Using cable method cast on 23 (23) (26) sts [94 (100) (112) sts].

Next row: purl.

Continue without further shaping until back measures 24 (25) (25·5) cm from beg ending with a wrong side row.

Next row: cast off 36 (39) (45) sts k 22 sts cast off rem 36 (39) (45) sts.

Leave rem 22 sts on a holder.

LEFT FRONT

With size 3 mm needles cast on 22 (25) (28) sts and work 2 rows in g st.

Change to size 3 $\frac{3}{4}$ mm needles and continue in st st (throughout) until front measures same as back to shape sleeve ending with a wrong side row.

**** Shape sleeve

See NOTE on back of Patterned Coat.

Using cable method cast on 23 (23) (26) sts [45 (48) (54) sts].

Continue in st st (and lace patt for Lacy Coat) until front measures 4 (4·5) (5) cm from cast on edge of sleeve ending with a right side row.

Shape neck

Next row: p 3 sts slip these 3 sts to a safety pin, p to end.

*** Work 6 rows dec one st at neck edge every row [36 (39) (45) sts].

Work without further shaping until front measures same as back ending with a wrong side row.

Cast off rem sts.

RIGHT FRONT

With size 3 mm needles cast on 22 (25) (28) sts and work 2 rows in g st.

Change to size 3 $\frac{3}{4}$ mm needles and continue in st st (throughout) until front measures same as back to shape sleeve ending with a right side row.

**** Shape sleeve

See NOTE on back of Patterned Coat.

Using cable method cast on 23 (23) (26) sts [45 (48) (54) sts].

Continue in st st (and lace patt for Lacy Coat) until front measures 4 (4·5) (5) cm from cast on edge of sleeve ending with a wrong side row.

Shape neck

Next row: k 3 sts slip these 3 sts to a safety pin k to end.

Next row: purl.

Complete as given from *** on left front of Plain Coat.

Work the shoulder inserts, sleeve edgings and front borders as given for Patterned Coat.

NECKBAND

With size 3 mm needles and right side of work facing k dec 3 sts evenly across right front border, k across 3 sts left on safety pin, pick up and k 10 sts up right front neck, k dec 3 sts evenly across right shoulder insert cable, k across 22 sts left on back neck holder, k dec 3 sts evenly across left shoulder insert cable, pick up and k 10 sts down left front neck, k across 3 sts left on safety pin and k dec 3 sts evenly across left front border [68 sts].

Work 2 rows in g st. Cast off.

LACY COAT

BACK

Work as given for back of Plain Coat.

LACE PANEL

(worked over 8 sts)

1st row: k1 (k2 tog yn fwd) 3 times k1.

2nd row: purl.

3rd row: k2 (k2 tog yn fwd) twice k2.

4th row: purl.

These 4 rows form lace patt panel.

LEFT FRONT

With size 3 mm needles cast on 22 (25) (28) sts and work 2 rows in g st.

Change to size $3\frac{3}{4}$ mm needles and commence patt **

1st row: k3 (6) (9) work 1st row of lace patt panel for next 8 sts k to end.

2nd row: purl.

Keeping 8 sts in patt (throughout) and rem sts in st st as set continue working from 3rd row of lace patt panel until front measures same as back to shape sleeve ending with a wrong side row.

Complete as given from **** on left front of Plain Coat.

RIGHT FRONT

Work as given from left front of Lacy Coat to **

1st row: k11 work 1st row of lace patt panel for next 8 sts k to end.

2nd row: purl.

Keeping 8 sts in patt (throughout) and rem sts in st st as set continue working from 3rd row of lace patt panel until front measures same as back to shape sleeve ending with a right side row.

Complete as given from **** on right front of Plain Coat.

Work the shoulder inserts, sleeve

edgings and front borders as given for Patterned Coat.

Thread ribbon through lace panels as illustrated securing evenly on the back with hem stitch.

NECKBAND

Work as given for Plain Coat.

TO MAKE UP

Press according to instructions on ball band.

Join side and underarm seams including cable border. Make two loops on edge of front cable border, on the right front border for a girl or the left front border for a boy. Sew on buttons to correspond with loops. Sew two more buttons on opposite border as illustrated. Make a bow and sew in position as illustrated.

Buttons by Jason. Ribbon by Offray.

YARN AMOUNTS

TEDDY WOOLS DOUBLE KNITTING

	Patterned Coat			Plain and Lacy Coats			
Chest	35	40	46	35	40	46	cm
	14	16	18	14	16	18	inch
TEDDY FAMILY DK	2	2	2	1	1	2	100 g balls
TEDDY CLASSIC DK	2	2	2	1	1	2	100 g balls
TEDDY SPRINGTIME DK	5	5	6	4	4	5	25 g balls
TEDDY BABY SOFTSPUN DK	1	2	2	1	1	1	100 g balls

Please buy sufficient yarn of one dyelot to complete your garment