

Aran Knitting

50-75 cms (20-30 ins)



Teddy

Knitting Yarns

7200



Children's Jackets

MEASUREMENTS AND MATERIALS: See back page

TENSION

17 sts and 36 rows = 10 cms [4 ins] square measured over garter st using 5 mm needles.

It is essential to obtain correct tension in yarn used and a small test piece should be worked. If piece measures **more** than required width try again using smaller needles. If piece measures **less** than required width try again using larger needles.

NOTES

Figures in round brackets refer to the larger sizes. Figures or instructions in square brackets, [], should be repeated as stated after the brackets.

The quantities of yarn stated are based on average requirements and are therefore approximate.

ABBREVIATIONS

Alt = alternate; beg = beginning; cms = centimetres; dec = decrease; foll = following; garter st = every row knit; inc = increase; ins = inches; k = knit; p = purl; patt = pattern; rem = remain(ing); rep = repeat; st(s) = stitch(es); tog = together; yf = yarn forward.

SPECIAL ABBREVIATIONS

C4B (Cable 4 Back) = slip next 2 sts onto cable needle and hold at back of work, k2, then k2 from cable needle.

T3F (Twist 3 Front) = slip next 2 sts onto cable needle and hold at front of work, p1, then k2 from cable needle.

T3B (Twist 3 Back) = slip next st onto cable needle and hold at back of work, k2, then p1 from cable needle.

CABLE PANEL

(Worked across 24 sts)

1st row (right side): K24.

2nd row: P4, [k6, p4] twice.

3rd row: C4B, [k6, C4B] twice.

4th row: P4, [k6, p4] twice.

5th row: K24.

6th row: P4, [k6, p4] twice.

7th row: C4B, [k6, C4B] twice.

8th row: P4, [k6, p4] twice.

9th row: K9, T3B, T3F, k9.

10th row: P4, k5, p2, k2, p2, k5, p4.

11th row: C4B, k4, T3B, k2, T3F, k4, C4B.

12th row: P4, k4, [p2, k4] twice, p4.

13th row: K7, T3B, k4, T3F, k7.

14th row: P4, k3, p2, k6, p2, k3, p4.

15th row: C4B, k16, C4B.

16th row: P4, k3, p2, k6, p2, k3, p4.

17th row: K7, T3F, k4, T3B, k7.

18th row: P4, k4, [p2, k4] twice, p4.

19th row: C4B, k4, T3F, k2, T3B, k4, C4B.

20th row: P4, k5, p2, k2, p2, k5, p4.

21st row: K9, T3F, T3B, k9.

22nd row: P4, [k6, p4] twice.

23rd row: C4B, [k6, C4B] twice.

24th row: P4, [k6, p4] twice.

These 24 rows form the cable panel.

ZIP FRONT JACKET BACK

Using 4mm needles cast on 54(59-64-68-73-77) sts and work 3 rows in garter st.

Next row (increase): K5(6-7-8-10-11), *[inc in next st, k3] 4 times, inc in next st*, k10(13-16-18-19-21), rep from * to * once more, k5(6-7-8-10-11). 64(69-74-78-83-87) sts.

Change to 5mm needles.

Next row: K4(5-6-7-9-10), [p4, k6] twice, p4, k8(11-14-16-17-19), [p4, k6] twice, p4, k4(5-6-7-9-10).

Commence Patt:-

1st row (right side): K4(5-6-7-9-10), work 1st row of cable panel across next 24 sts, k8(11-14-16-17-19), work 1st row of cable panel across next 24 sts, k4(5-6-7-9-10).

2nd row: K4(5-6-7-9-10), work 2nd row of cable panel, k8(11-14-16-17-19), work 2nd row of cable panel, k4(5-6-7-9-10).

These 2 rows form garter st at either side and between cable panels. Cont thus, working appropriate rows of cable panels until Back measures 38(42-46-50-54-58) cms, ending with a wrong side row.

Shape Shoulders

Cast off 8(8-9-10-10-11) sts at beg of next 4 rows, then 7(9-9-9-11-10) sts at beg of foll 2 rows. Cast off rem 18(19-20-20-21-23) sts.

SLEEVES

Using 4mm needles cast on 31(31-33-35-35-37) sts and work 14 rows in garter st. Tie a marker to each end of last row.

Next row (right side): K1. *p1, k1; rep from * to end.

Next row: P1, *k1, p1; rep from * to end.

Rep the last 2 rows 3 times more.

Change to 5mm needles and working in garter st throughout, work 6 rows straight. Inc 1 st at each end of next and every foll 10th row until there are 41(45-49-53-57-61) sts. Work straight until sleeve measures 24(29-33-37-40-44) cms from cast-on edge, or 4 cms more than required seam length. Cast off.

LEFT FRONT

Using 4mm needles cast on 27(29-32-34-36-38) sts and work 3 rows in garter st.

Next row (increase): K5(6-7-8-10-11), [inc in next st, k3] 4 times, inc in next st, k5(6-8-9-9-10). 32(34-37-39-41-43) sts.

Change to 5mm needles.

Next row: K4(5-7-8-8-9), [p4, k6] twice, p4, k4(5-6-7-9-10).

Commence Patt:-

1st row (right side): K4(5-6-7-9-10), work 1st row of cable panel across next 24 sts, k4(5-7-8-8-9).

2nd row: K4(5-7-8-8-9), work 2nd row of cable panel, k4(5-6-7-9-10).

Working appropriate rows of cable panels work 8 more rows.

Divide for Pocket

Next row: K3(4-5-6-8-9), turn and slip rem 29(30-32-33-33-34) sts onto a holder.

Next row: Cast on 19 sts for pocket lining, k these sts, then k to end.

Work 31(31-35-35-39-39) rows in garter st on these 22(23-24-25-27-28) sts, thus ending with a right side row.

Next row: Cast off 19 sts, break yarn and slip rem 3(4-5-6-8-9) sts onto a holder.

With right side facing rejoin yarn to sts on first holder and work in patt to end.

Work 32(32-36-36-40-40) rows in patt on these 29(30-32-33-33-34) sts, thus ending with a right side row.

Next row: Patt to end, then knit across sts on holder. 32(34-37-39-41-43) sts.

★ Cont in patt until Front is 15(15-17-17-19-19) rows shorter than Back to start of shoulder shaping (work 1 row more here for Right Front), thus ending at front edge.

Shape Neck

Next row: Cast off 3(3-3-3-3-4) sts, patt to end.

Keeping patt correct dec 1 st at neck edge on next 3 rows, then every alt row 3(3-4-4-4-4) times. 23(25-27-29-31-32) sts. Work 5(5-5-5-7-7) rows straight, thus ending at side edge.

Shape Shoulder

Cast off 8(8-9-10-10-11) sts at beg of next and foll alt row. Work 1 row. Cast off rem 7(9-9-9-11-10) sts.

RIGHT FRONT

Using 4mm needles cast on 27(29-32-34-36-38) sts and work 3 rows in garter st.

Next row (increase): K5(6-8-9-9-10), [inc in next st, k3] 4 times, inc in next st,

k5(6-7-8-10-11). 32(34-37-39-41-43) sts.
Change to 5mm needles.

Next row: K4(5-6-7-9-10), [p4, k6] twice, p4, k4(5-7-8-8-9).

Commence Patt:-

1st row (right side): K4(5-7-8-8-9), work 1st row of cable panel across next 24 sts, k4(5-6-7-9-10).

2nd row: K4(5-6-7-9-10), work 2nd row of cable panel, k4(5-7-8-8-9).

Working appropriate rows of cable panels work 8 more rows.

Divide for Pocket

Next row: Patt 29(30-32-33-33-34) sts, turn and slip rem 3(4-5-6-8-9) sts onto a holder.

Work 32(32-36-36-40-40) rows in patt on these 29(30-32-33-33-34) sts, thus ending with a right side row. Break yarn and slip sts onto a holder.

Next row: Cast on 19 sts for pocket lining, k these sts, then k across sts on first holder.

Work 31(31-35-35-39-39) rows in garter st on these 22(23-24-25-27-28) sts, thus ending with a wrong side row.

Next row: Cast off 19 sts, k to end.

Next row: K to end, then patt across sts on holder. 32(34-37-39-41-43) sts.

Complete to match Left Front from ★ to end reversing shaping by working 1 row more where indicated.

HOOD (Optional)

Using 4mm needles cast on 95(102-109-116-123-130) sts and work 3 rows in garter st.

Next row: K5, *inc in next st, k6; rep from * to last 6 sts, inc in next st, k5. 108(116-124-132-140-148) sts.

Change to 5mm needles and commence patt:-

1st row (wrong side): K4, *p4, k4; rep from * to end.

2nd row: Knit.

3rd row: K4, *p4, k4; rep from * to end.

4th row: K4, *C4B, k4; rep from * to end.

These 4 rows form the patt. Keeping patt correct work 1 more row. Dec 1 st at each end of next and every alt row until 92(100-108-116-124-132) sts rem. Work straight until hood measures 14(15-16-17-18-19) cms ending with a wrong side row.

Shape Back

Cast off 3 sts at beg of next 12(12-14-14-16-16) rows. Cast off rem 56(64-66-74-76-84) sts.

COLLAR (Optional)

Using 4mm needles cast on 69(73-79-83-89-93) sts.

1st row (right side): K1, *p1, k1; rep from * to end.

2nd row: P1, *k1, p1; rep from * to end.

Rep the last 2 rows until Collar

measures 5(5-6-6-7-7) cms ending with a wrong side row.

Cast off 6(6-7-7-8-8) sts in rib at beg of next 8 rows. Cast off rem 21(25-23-27-25-29) sts in rib.

FINISHING AND EDGINGS

Read pressing instructions on ball band.

Pocket Edgings: Using 4mm needles and with right side facing pick up and k19(19-21-21-23-23) sts evenly along side edge of pocket opening.

Starting with the 2nd row work 3(3-5-5-5-5) rows in k1, p1 rib as given for Collar. Cast off in rib.

Sew pocket linings and edgings in place. Join shoulder seams. Fold sleeves in half lengthways and mark centre of cast off edge. Sew sleeve to side edge placing centre at shoulder seam. Join side and sleeve seams reversing seam on lower 4 cms of garter st of sleeve. Turn back cuffs along marked row. Sew shaped edge of collar to neck edge **or** join back seam of hood and sew to neck edge easing in hood across back neck. Sew in zip fastener.

JACKET WITH BUTTONS BACK, SLEEVES AND HOOD OR COLLAR

Work as given for Back, Sleeves and Hood or Collar of Zip Front Jacket.

GIRL'S LEFT FRONT

★ Using 4mm needles cast on 30(32-35-37-39-41) sts and work 3 rows in garter st.

Next row (increase): K5(6-7-8-10-11), [inc in next st, k3] 4 times, inc in next st, k8(9-11-12-12-13). 35(37-40-42-44-46) sts.

Change to 5mm needles.

Next row: K7(8-10-11-11-12), [p4, k6] twice, p4, k4(5-6-7-9-10).

Commence Patt:-

1st row (right side): K4(5-6-7-9-10), work 1st row of cable panel across next 24 sts, k7(8-10-11-11-12).

2nd row: K7(8-10-11-11-12), work 2nd row of cable panel across next 24 sts, k4(5-6-7-9-10).

Working appropriate rows of cable panels, work 8 more rows.

Divide for Pocket

Next row: K3(4-5-6-8-9), turn and slip rem 32(33-35-36-36-37) sts onto a holder.

Next row: Cast on 19 sts for pocket lining, k these sts, then k to end.

Work 31(31-35-35-39-39) rows in garter st on these 22(23-24-25-27-28) sts, thus ending with a right side row.

Next row: Cast off 19 sts, break yarn and slip rem 3(4-5-6-8-9) sts onto a holder.

With right side facing rejoin yarn to sts on first holder and work in patt to end.

Work 32(32-36-36-40-40) rows in patt on these 32(33-35-36-36-37) sts, thus ending with a right side row.

Next row: Patt to end, then k across sts on holder. 35(37-40-42-44-46) sts ★.

Cont in patt until Front is 15(15-17-17-19-19) rows shorter than Back to start of shoulder shaping (work 1 row more here for Right Front), thus ending at front edge.

Shape Neck

Next row: Cast off 6(6-6-6-6-7) sts, patt to end.

Keeping patt correct dec 1 st at neck edge on next 3 rows, then every alt row 3(3-4-4-4-4) times. 23(25-27-29-31-32) sts rem. Work 5(5-5-5-7-7) rows straight, thus ending at side edge.

Shape Shoulder

Cast off 8(8-9-10-10-11) sts at beg of next and foll alt row. Work 1 row. Cast off rem 7(9-9-9-11-10) sts.

Mark positions at front edge for 5(6-6-7-7-8) buttons, the first 3 cms above cast on edge and the top one to be 1 cm below start of neck shaping. Space remainder evenly between

GIRL'S RIGHT FRONT

★★ Using 4mm needles cast on 30(32-35-37-39-41) sts and work 3 rows in garter st.

Next row (increase): K8(9-11-12-12-13), [inc in next st, k3] 4 times, inc in next st, k5(6-7-8-10-11). 35(37-40-42-44-46) sts.

Change to 5mm needles.

Next row: K4(5-6-7-9-10), [p4, k6] twice, p4, k7(8-10-11-11-12).

Making buttonholes to match markers on right side rows throughout as follows:- K3, yf, k2tog, patt to end, commence patt:-

1st row (right side): K7(8-10-11-11-12), work 1st row of cable panel across next 24 sts, k4(5-6-7-9-10).

2nd row: K4(5-6-7-9-10), work 2nd row of cable panel, k7(8-10-11-11-12).

Working appropriate rows of cable panels, work 8 more rows.

Divide for Pocket

Next row: Patt 32(33-35-36-36-37) sts, turn slip rem 3(4-5-6-8-9) sts onto a holder.

Work 32(32-36-36-40-40) rows in patt on these 32(33-35-36-36-37) sts, thus ending with a right side row. Break yarn and slip sts onto a holder.

Next row: Cast on 19 sts for pocket lining, k these sts, then k across sts on first holder.

Work 31(31-35-35-39-39) rows in garter st on these 22(23-24-25-27-28) sts, thus ending with a wrong side row.

Next row: Cast off 19 sts, k to end.

Next row: K to end, then patt across sts on holder. 35(37-40-42-44-46) sts. ★★

Complete to match Left Front reversing shaping by working 1 row more where indicated.

BOY'S RIGHT FRONT

Work as given for Girl's Right Front from ★★ to ★★ omitting buttonholes.

Cont in patt until Front is 14(14-16-16-18-18) rows shorter than back to start of shoulder shaping (work 1 row less here for Left Front), thus ending at front edge.

Shape Neck

Next row: Cast off 6(6-6-6-6-7) sts, patt to end.

Keeping patt correct dec 1 st at neck edge on next 3 rows, then every alt row 3(3-4-4-4-4) times. 23(25-27-29-31-32) sts. Work 5(5-5-5-7-7) rows straight, thus ending at side edge.

Shape Shoulder

Cast off 8(8-9-10-10-11) sts at beg of next and foll alt row. Work 1 row. Cast off rem 7(9-9-9-11-10) sts.

Mark positions at front edge for 5(6-6-7-7-8) buttons, the first 3 cms above cast on edge and the top one to be 1 cm below start of neck shaping. Space remainder evenly between

BOY'S LEFT FRONT

Work as given for Girl's Left Front from ★ to ★ **at the same time** making buttonholes to match markers on right side rows throughout as follows:- patt to last 4 sts, yf, k2tog, k2.

Complete to match Right Front reversing shaping by working 1 row less where indicated.

FINISHING AND EDGINGS

Read pressing instructions on ball band.

Pocket Edgings: Work as given for Zip Front Jacket.

Sew pocket linings and edgings in place. Join shoulder seams. Fold sleeves in half lengthways and mark centre of cast off edge. Sew sleeve to side edge placing centre at shoulder seam. Join side and sleeve seams reversing seam on lower 4 cms of garter st of sleeve. Turn back cuffs along marked row. Sew shaped edge of collar to neck edge **or** join back seam of hood and sew to neck edge easing in hood across back neck. Sew on buttons.

To Fit

Chest sizes	50	55	60	65	70	75	cms
	20	22	24	26	28	30	ins
Finished measurement	63	69	74	79	85	90	cms
	25	27½	29½	31½	34	36	ins
Length to shoulder	38	42	46	50	54	58	cms
	15	16½	18	19½	21	23	ins
Sleeve seam	20	25	29	33	36	40	cms
	8	10	11½	13	14	16	ins

Materials

Teddy Vanguard Aran 100g balls

Jacket with Hood	4	4	5	6	7	8	balls
Jacket with Collar	4	4	5	5	6	7	balls

Teddy Classic Aran 400g balls

Jacket with Hood	1	1	2	2	2	2	balls
Jacket with Collar	1	1	2	2	2	2	balls

Pair needles each size 5mm (UK 6 - USA 8) and 4mm (UK 8 - USA 6). Cable needle. 5(6-6-7-7-8) buttons or open-ended zip fastener approximately 35(35-40-45-50-50) cms to fit front opening.