



www.LionBrand.com

Pierrot's sweater is featured on page 94.
See Patterns section for instructions.

theberet&muff



SIZES

- Beret fits 20"/51cm to 22"/56cm head measurement.
- Muff measures 12 1/2"/32cm, side to side and 5 1/2"/14cm, from top to bottom.

MATERIALS

- 1 6oz/170g ball (each approx 106yd/97m) of Lion Brand Wool-Ease® Thick & Quick® (acrylic/wool) in #100 White (A)
- 3 1 1/2oz/50g balls (each approx 64yd/58m) of Lion Brand Fun Fur (polyester) in #100 White (B)
- One pair size 15 (10mm) needles OR SIZE TO OBTAIN GAUGE

For beret only

- Crochet hook size K/10 1/2 (6.5mm)
- Stitch markers

GAUGE

8 sts and 11 rows = 4"/10cm over St st using size 15 (10mm) needles with 1 strand A and 3 strands B held tog. TAKE TIME TO CHECK GAUGE.

BERET

With size 15 (10mm) needles and A, cast on 69 sts for crown. Add 3 strands of B and hold tog with A. Work in reverse St st as follows:

Next row (WS) K9, *place marker, k17, rep from * twice more, end place marker, k9.

Next row *P to 2 sts before marker, p2tog, sl marker; rep from * twice more, sl marker, p to end—65 sts.

Next row *K to 2 sts before marker, k2tog, sl marker; rep from * to twice more, sl marker, k to end—61 sts.

Rep last 2 rows 7 times more—5 sts rem.
Cut B. Run A through rem 5 sts, pull tight. Cut A, leaving a length for sewing. With A, sew back seam.

CROCHETED BRIM

With RS facing and crochet hook, join A with sl st to cast-on edge of crown at back seam.

Rnd 1 Ch 3, work dc in every other cast-on st—34 dc, join with sl st to top of beg ch-3.

Rnd 2 Ch 3, skip first dc, dc in each dc around—34 dc, join with sl st to first dc.

Rnd 3 Ch 1, sc in each dc around—34 sc, join with sl st to first sc. Fasten off.

MUFF

With size 15 (10mm) needles and A, cast on 26 sts.

Row 1 (RS) Sl 1, k2, add 3 strands B and hold tog with A, k20, drop B, with A only k3.

Row 2 Sl 1, p2, pick up 3 strands B and hold tog with A, p20, drop B, with A only p3.

Rep rows 1 and 2 until muff measures 11 1/2"/29cm, end with a WS row. Drop B, loosely bind off knitwise with A.

FINISHING

With WS facing out, sew cast-on edge to bound-off edge. Turn inside out so that the rev St st side is the right side.

We have made every effort to ensure the accuracy of the contents of this publication. We are not responsible for any human or typographical errors.

theberet&muff

